

The image shows the ESP8266 Pin Header Expansion Board with the following pin configurations:

Pin	Function
1	3.3V
2	EN
3	RESET
4	ADC0
5	ADC3
6	ADC6
7	ADC7
8	ADC4
9	DAC1
10	TOUCH9
11	DAC8
12	TOUCH8
13	DAC7
14	TOUCH7
15	DAC6
16	TOUCH6
17	DAC5
18	TOUCH5
19	TOUCH4
20	RX1
21	TX1
22	FLASH D3
23	FLASH CMD
24	Vin 5V
25	GND
26	GIO P13
27	GIO P9
28	GIO P10
29	GIO P11
30	EN
31	IO0
32	GND
33	GIO P23
34	VSPI MOSI
35	GIO P22
36	12C SCL
37	GIO P1
38	TX0
39	GIO P3
40	RX0
41	GIO P21
42	12C SDA
43	GND
44	GIO P19
45	VSPI MISO
46	GIO P18
47	VSPI SCK
48	GIO P5
49	VSPI SS
50	GIO P17
51	TX2
52	GIO P16
53	RX2
54	GIO P4
55	ADC10
56	TOUCH0
57	GIO P0
58	ADC11
59	TOUCH1
60	GIO P2
61	ADC12
62	TOUCH2
63	GIO P15
64	ADC13
65	TOUCH3
66	GIO P7
67	FLASH D1
68	GIO P8
69	FLASH D0
70	GIO P6
71	FLASH CK